

LED DOWNLIGHT LOGIC ECO G2

LEDIGAMI LED DOWNLIGHT LOGIC ECO G2 provides control over the perfect ambience, it has a broad portfolio with CCT from 3000K, 4000K and 6500K with the minimum of CRI 80.

LED DOWNLIGHT LOGIC ECO G2 comes with round versions with 6 different dimensions for selection, The elegant design enables applications to be installed in places like offices, shopping centres and living rooms.



FEATURES

- System Power : 9W, 12W, 15W, 20W, 25W & 35W
- Outer Dimension (mm) : Ø100, Ø120, Ø145, Ø165, Ø180 & Ø230
- Beam Angles : 100°
- CCT : 3000K, 4000K, & 6500K
- CRI : 80
- IP Rating : IP20

HIGHLIGHTS

- Easy maintenance and Installation
- LED lifespan up to 50,000hrs @ L70B50
- Instant-On Light

CERTIFICATIONS

- CE
- RoHS

TECHNICAL SPECIFICATIONS

Power	CCT	Beam Angles	Light Output	CRI	Outer Dimension	Cut-Out Size	Article Number
9W	3000/4000/6500K	100°	900lm	80	Ø100 x 33mm	Ø75mm	LC-DR-PeT-GxAMBA
12W	3000/4000/6500K	100°	1200lm	80	Ø120 x 33mm	Ø100mm	LC-DR-UeN-GxAMBA
15W	3000/4000/6500K	100°	1500lm	80	Ø145 x 34mm	Ø125mm	LC-DR-ceD-GxAMBA
20W	3000/4000/6500K	100°	2000lm	80	Ø165 x 34mm	Ø145mm	LC-DR-ke2-GxAMBA
25W	3000/4000/6500K	100°	2500lm	80	Ø180 x 35mm	Ø165mm	LC-DR-qeE-GxAMBA
35W	3000/4000/6500K	100°	3500lm	80	Ø230 x 36mm	Ø200mm	LC-DR-MpF-GxAMBA

Option : x = CCT
C= 3000K D=4000K F=6500K

Note :
All measurement datas are subjected to 10% tolerance due to measurement equipment tolerance and accuracy
Lumen maintenance factor : L70B80 @ normal temperature (25 degree C)
All product specifications are subject to change without prior notice

