LEDIGAMI

LED DOWNLIGHT LUXURUS

LEDIGAMI LED DOWNLIGHT LUXURUS provides control over the perfect ambience, it has a broad portfolio with CCT from 3000K, 4000K, and 6000K with the minimum of 80 CRI.

LED DOWNLIGHT LUXURUS comes with round versions with 5 different dimensions to choose from. The elegant design enables applications to be installed in places like offices, shopping centers, meeting rooms and etc.



SPECIFICATIONS

- System Power: 7W, 10W, 15W, 25W & 35W
- Outer Dimensions: Φ90mm, Φ115mm, Φ140mm, Φ200 & Φ230mm
- CCT: 3000K, 4000K, 6500K
- CRI: 80
- Life Span: 40K Hours
- IP Rating: IP20


HIGHLIGHTS

- High reduction in power consumption
- Elegant Design
- Instant-on light
- Optional Dimming function (0/1-10V or DALI)

CERTIFICATIONS

- CE
- RoHS





Tolerance: ±2.5mm

System Power	ССТ	Beam Angles	Light Output	CRI	LED Type	Outer Dimensions	Cut-out Size	Article Number
7W	3000K	40°	651lm	80	COB	Ф90 x H52mm	65mm	LC-DL-CAB-BCFEBB
7W	4000K	40°	700lm	80	COB	Ф90 x H52mm	65mm	LC-DL-CAB-BDFEBB
7W	6500K	40°	700lm	80	COB	Ф90 x H52mm	65mm	LC-DL-CAB-BFFEBB
10W	3000K	40°	930lm	80	COB	Ф115 x H65mm	90mm	LC-DL-DAC-BCFEBB
10W	4000K	40°	1000lm	80	COB	Ф115 x H65mm	90mm	LC-DL-DAC-BDFEBB
10W	6500K	40°	1000lm	80	COB	Ф115 x H65mm	90mm	LC-DL-DAC-BFFEBB
15W	3000K	40°	1395lm	80	COB	Ф140 x H76mm	115mm	LC-DL-EAD-BCFEBB
15W	4000K	40°	1500lm	80	COB	Ф140 x H76mm	115mm	LC-DL-EAD-BDFEBB
15W	6500K	40°	1500lm	80	COB	Ф140 x H76mm	115mm	LC-DL-EAD-BFFEBB
25W	3000K	40°	2535lm	80	COB	Ф200 x H108mm	160mm	LC-DL-FAE-BCFEBB
25W	4000K	40°	2500lm	80	COB	Ф200 x H108mm	160mm	LC-DL-FAE-BDFEBB
25W	6500K	40°	2500lm	80	COB	Ф200 x H108mm	160mm	LC-DL-FAE-BFFEBB
35W	3000K	40°	3255lm	80	COB	Ф230 x H120mm	195mm	LC-DL-GAF-BCFEBB
35W	4000K	40°	3500lm	80	COB	Ф230 x H120mm	195mm	LC-DL-GAF-BDFEBB
35W	6500K	40°	3500lm	80	COB	Ф230 x H120mm	195mm	LC-DL-GAF-BFFEBB

Note

All measurement datas are subjected to 10% tolerance due to measurement equipment tolerance and accuracy

All product specifications are subject to change without prior notice