

LED PANEL LIGHT LATUS DE

LATUS DE adopts qualified super bright LED as light source, it provides a commitment of stable, long life and no UV and IR emission. The frame is designed to be modern and stylish, while the high quality frosted cover is used for efficient light diffusion.

LATUS DE is the ideal replacement for traditional grid lights and fluorescent tubes. It creates excellent light that conventional light will never achieve. It is suitable to be installed in hospital, offices, schools and warehouses.



SPECIFICATIONS


- Power : 40W
- Beam Angles : 120°
- CCT : 3000K, 4000K & 6500K
- CRI : 80
- IP Rating : IP20

HIGHLIGHTS

- Flicker-Free LED Driver
- Instant-on light
- LED direct backlighting without light guide
- 600 x 1200 mm panel available upon request
- Easy and various installation styles

CERTIFICATIONS

- CE
- RoHS



TECHNICAL SPECIFICATIONS

Power	CCT	Beam Angle	Light Output	Optics	CRI	Dimmable	Dimensions (H x W x T mm)	Voltage	Versions	Body Color	Art.-No.
40W	3000K	120°	3400lm	FROST	80	NO	600 x 600 x 30	220-240V	LED Direct Emitting	WHITE	HC-PD-YCL-NCAKBF
40W	4000K	120°	4000lm	FROST	80	NO	600 x 600 x 30	220-240V	LED Direct Emitting	WHITE	HC-PD-YCL-NDAKBF
40W	6500K	120°	4000lm	FROST	80	NO	600 x 600 x 30	220-240V	LED Direct Emitting	WHITE	HC-PD-YCL-NRAKBF

* Instant light up < 1 second.

* Not suitable for accent lighting.

* All measurement data subjected to 10% tolerance due to measurement equipment tolerance and accuracy.

* Lumen maintenance factor : L70

** Product specification subjects to change without prior notice.